

Stands on end to fit into elevator



HY-FLEX
CORP

INDUSTRY PROVEN SINCE 1970

Optional Air Compressor



**PROVEN
RELIABILITY**

PORTABILITY & PRODUCTION WITHOUT COMPROMISE

HZ-30E

Proven inverter drive technology

Electric variable speed control

30" Hopper height

220 volt
30 Amp
single
phase

Rugged tubular frame

Fits though
36" doorway

Very low daily maintenance

Large rear wheels

Optimized 2L6 rotor & stator

10" Pneumatic casters

Entire hopper bottom removes for cleanout

**FIREPROOFING - STUCCO - EIFS - PLASTER - GROUT - CEMENT COATINGS
SPRAYING AND MIXING EQUIPMENT**

TOLL FREE 866.849.6246

www.HYFLEXCORP.com

SPECIFICATIONS & CAPACITIES

Power	5 HP Variable Speed
Power Requirement	208/240 V 30A
	1 or 3 Phase
Air Output (optional)	12 cfm
Pump Size	Optimized 2L6
Hopper Capacity	60 Gal
Hopper Height	32" / 81 cm
Volume Control	Variable 0-10 gpm
Pressure Outout	500 PSI Maximum
Directional Control	Forward and Reverse
Controls	Manual/Remote
Machine Width	33" / 839 cm
Machine Length	72" / 1829 cm
Machine Height	43" / 1092 cm
Machine Weight	585 lbs / 266 kg
Wheels - Rear	15" / 38cm OD Pneumatic
Wheels - Front	10" / 25cm OD Pneumatic Casters
Max Aggregate Size	.125" / 3 mm
Max Pumping Distance	200' (Note: It can be greater or less)
Optional Equipment	Air Compressor



HZ-30E



321E

321E Specifications and Capacities

Power	15 HP Electric	Controls	Manual/Remote
Power Requirement	208/230 volt 50A 3 PH	Directional Control	Forward and Reverse
Pump Type	3" Dual Piston	Machine Width	28" / 71 cm
Air Output	12 cfm	Machine Length	62" / 157 cm
Pump Size	2" Ball Valve	Machine Height	34" / 86 cm
Pump Output	70 Bags Per Hour	Machine Weight	1350 lbs / 615 kg
Hopper Height	23" / 58 cm	Wheels	8" Rigid and Swivel Casters
Volume Control	Variable Hydraulic	Max Aggregate Size	.187 in / 5 mm
Pressure Outout	1000 psi / adjustable	Max Pumping Distance	550' maximum



CM71

CM71 Specifications and Capacities

Power	3 HP	Machine Width	28" / 71cm - 30" / 76cm (with Platform)
Power Requirement	230 V Single Phase 20A	Machine Length	92.5" / 235 cm (with 40" mix tube)
Mixer Output	70 Bags Per Hour	Machine Height	70.5" / 179 cm
Hopper Capacity	3 Bags	Machine Weight	693 lbs / 314 kg
Charge Height	54" / 137 cm	Wheels	8" Rigid and Swivel Casters
Volume Control	Single Speed	Optional Equipment	Water System
Max Aggregate Size	Fireproofing		Work Platform

HF-15 SPRAY BUDDY



Spray Buddy Specifications and Capacities

Power	1 HP Electric	Controls	Manual/Remote
Power Requirement	110 Volt 15A	Machine Width	26" / 66cm
Pump Type	Optimized 2L3 Stator	Machine Length	54" / 137cm
Hopper Capacity	15 Gallon	Machine Height	41" / 104cm
Hopper Height	32" / 81cm	Machine Weight	190 lbs / 86kg
Volume Control	Variable 0-2 gpm	Wheels	12" OD Semi-Solid
Pressure Outout	200 PSI	Max Aggregate Size	.125" / 3 mm
Directional Control	Forward/Reverse	Max Pumping Distance	150' (Note: It can be greater or less)



HZ-30G

30G Specifications and Capacities

Power	13 HP Honda Gas Engine	Controls	Manual/Remote
Fuel Tank	1.7 Gal / 6.9 qts	Machine Width	33" / 84cm (48" / 122cm w/Tow Package)
Pump Output	0-10 gpm	Machine Length	84" / 213cm
Pump Size	Optimized 2L6	Machine Height	42" / 107cm
Air Output	12 cfm @ 90 psi	Machine Weight	675 lbs / 306 kg
Hopper Capacity	60 Gal	Wheels - Rear	20" OD Pneumatic
Hopper Height	30 in / 76 cm	Wheels - Front	10" OD Pneumatic Casters
Volume Control	Variable 0-10 gpm	Max Aggregate Size	.125 in / 3 mm
Pressure Output	500 PSI Maximum	Max Pumping Distance	200' (Note: It can be greater or less)
Directional Control	Forward and Reverse	Optional Equipment	Tow Package